

PolyPVC Black

Fast Dry Solvent Ink



PolyPVC series of inks are suitable for printing on non-porous and semi porous media. Delivered in HP 45 ink cartridges, PolyPVC inks are suited for barcodes, date codes, and other low density image printing applications. Available in spot colors.

PolyPVC is specially designed to print on plain PVC substrates including PVC shrinkwrap, but will dry instantly and have good adhesion to many substrates.

PolyPVC inks require minimal maintenance and are easily recoverable, but are best suited for continuous printing applications. Vacuum or air flow directly on the nozzles will affect startup performance.

General Performance Data

Property	Range	Comment
Optical Density (600x300)	1.1 – 1.2	Uncoated PVC
Dry Time	< 5 seconds	Uncoated PVC
Durability	Excellent	
Water Resistance	Excellent	
Rub Resistance	Excellent	
Shelf Life	3 months	
Target Substrates	PVC & PVC derivatives	



www.imtech-or.com

PolyPVC Black

Fast Dry Solvent Ink

Recommended Cartridge Operating Parameters

Property	Range	Comment
Operating Voltage	11 V	
Pulse Width	1.2 μ S	
Operating Frequency	6-12 KHz	
Pulse Warming Temperature	45 C	
Maximum Print Speed	800,000 drops/seconds	Thermal limit
Bulk Ink Application	TBD	
Storage Temperature	10 C – 30 C	For extended shelf life store cartridges in a refrigerator

Cartridge Maintenance and Handling

- Clean the printhead by wiping it with a lint free cloth moistened with denatured alcohol. Wipe slowly and lightly along the long edge with the printhead facing down.
- Store the cartridge upright with the supplied cap in place.

Disclaimer

WE DECLARE OUR LIABILITY TO BE THE PRICE OF THE CARTRIDGE. We are committed to a continuing program of product improvement. Thus, please be advised that specifications, performance, parameters and appearance of our products are subject to change without notice. The information (including performance parameters) provided about this ink is based on tests conducted under controlled conditions. Since conditions of actual use may differ and are beyond our control, use this ink at your own risk and test for suitability in the application. We only guarantee initial start-up of the cartridge prior to the use by date listed on the cartridge packaging.

MSDS IS AVAILABLE UPON REQUEST.



IMTECH
Experts In Inkjet

www.imtech-or.com